



# Rolling Stage

Product Specific Brochure

[www.prolyte.com](http://www.prolyte.com)



# Rolling Stage

## STRENGTH ON WHEELS

### Product Description

The Prolyte Rolling Stage is designed for versatility and ease of use, making it suitable for regular and elevated stage setups. Its modular, foldable design reduces setup time and offers an efficient, customizable staging solution for events of all sizes. The load-bearing wheels enable the entire stage to be rolled with the maximum allowable load.

With the rotatable 4-way adapters, all stage configurations can be built without the necessity of changing adapters per setup.

Not every deck requires its own support frame. This creates open pathways beneath the stage, ideal for storage or equipment setups.

#### Technical Specifications – Rolling Stage

Alloy	EN AW 6082 T6
Main profile	70x70x4mm
Diagonal members	50x4mm
Deck adapter	S355 steel
Wheels	200mm diameter



\*The Rolling Stage is finished in standard aluminium. Black powder coating is available on request.

#### SM-F-R series standard available frames and accessories

Item Number	Code	Description
115900058	SM-FR-200100-150	Rolling frame 200x100cm, height adjustable 150-220cm
115900061	PC-SM-FR-200100-150-RAL9005	Rolling frame 200x100cm, height adjustable 150-220cm RAL9005
115900057	SM-FR-ADAP-04	Rolling frame 4-way rotatable adapter

#### SM-F-R series standard available spare parts

Item Number	Code	Description
115900059	SM-FR-ADJ-LEG-02	Rolling frame extendable leg 150-220cm
115900062	PC-SM-FR-ADJ-LEG-02-RAL9005	Rolling frame extendable leg 150-220cm RAL9005
115310015	SM-F-A-LP16	Locking pin for easyframe
115330017	SM-F-C-ADAP-01	Deck to frame adapter 48mm
111520084	BM-M12X035-IB	Bolt M12x035 hexagon DIN912

# Rolling Stage

## Advantages:

- **Load-Bearing Wheels:** The wheels are load-bearing, enabling the complete stage to roll with the maximum allowable load on it.
- **Quick Assembly:** Tool-less assembly allows for faster and simpler setup, minimizing build times.
- **Modular Base System:** Built with durable frames, forming standard 200x100 cm modules for flexible stage configurations. The Rolling Stage can be double stacked to extend the stage by 1 deck. Even and uneven stages can be built with 1 type of frame.
- **Rotatable 4-way adapters:** All stage configurations can be built without the necessity of changing adapters per setup.
- **Height Adjustability:** The system offers height settings from 150 cm to 220 cm in 5 cm increments.
- **Foldable Design:** The entire system is foldable, enhancing portability and storage efficiency.
- **Efficient Space Utilization:** Not every deck requires its own support frame, enabling open pathways below the stage for storage or equipment setups.
- **Robust Loading Capacity:** Supports up to 500 kg/m<sup>2</sup>, providing the strength needed for heavy equipment and demanding setups.



Tool-less  
assembly





**Prolyte B.V.**  
**Industriepark 9**  
**9351 PA Leek**  
**Netherlands**

**T: +31-594 851 515**  
**[sales@prolyte.com](mailto:sales@prolyte.com)**



**[www.prolyte.com](http://www.prolyte.com)**